

PRODUCT DATA SHEET



Concrete Form Oil | Industrial Oil

Product Description

Marathon Concrete Form Oil is a mineral-oil-based, low viscosity form release agent. It is amber colored and can be used in a variety of form release applications. This product enables easy form removal and a smooth concrete finish, by preventing buildup of concrete on metal, fiberglass, plastic, or wood forms.

Marathon Concrete Form Oil can be brushed, sponged, or sprayed on¹.

Features

- Rust and Oxidation protection to metal forms
- Clean separation forms
- Ideal cold temperature properties
- Sulfur and zinc free mold release agents²

Technical Data (Typical values)

ISO Grade	ASTM	22
Product Numbers		1070 (bulk)
Viscosity @ 40°C, cSt	D445	21.4
Specific Gravity @ 60°F	D4052	0.855
Pour Point, °C	D5950	-15
Flash Point, °C	D92	190
Copper Corrosion	D130	1A
Color ASTM	D1500	L0.5

(1) Always apply in a well-ventilated area

(2) With time, additives tend to separate and drop to the bottom. Mix well before use

The recommended shelf life for these oils is typically 12 months from manufacturing date when stored properly in the original sealed containers.

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Marathon Petroleum Company believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.