SAFETY DATA SHEET



1. IDENTIFICATION

Product Name Marathon Pro EP Gear Oil Full Syn

Synonym Marathon Pro EP Full Synthetic Gear Oil; Marathon Pro EP Gear Oil Full Syn 220;

Marathon Pro EP Gear Oil Full Syn 460

Product code 0644MAR019

Chemical family Hydrocarbon Mixture

Recommended use Lubricant.
Restrictions on use All others.

Manufacturer, Importer, or Responsible Party Name and

Responsible Party Name and Address

MARATHON PETROLEUM COMPANY LP

539 South Main Street Findlay, OH 45840

SDS information 1-419-421-3070 (M-F; 8-5 EST)

24 Hour Emergency Telephone CHEMTREC: 1-800-424-9300 (CCN# 13740)

2. HAZARD IDENTIFICATION

OSHA Regulatory Status

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Classification

Not classified

Hazards Not Otherwise Classified (HNOC)

Not applicable

2.2. Label Elements

No known significant effects or critical hazards.

Appearance Amber Liquid Physical State Liquid Odor Petroleum

Precautionary Statements - Prevention

Not applicable

Precautionary Statements - Response

Not applicable

Precautionary Statements - Storage

Not applicable

Precautionary Statements - Disposal

SDS ID NO.: 0644MAR019 Product name Marathon Pro EP Gear Oil Full Syn Page 1 of 8

·

Revision date 07/18/2025

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Additional Information

This SDS contains valuable information critical to the safe handling and proper use of the product. The SDS should be retained and available for employees and other users of this product. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition Information

| Chemical Name | CAS Number | % Concentration |
|---|------------|-----------------|
| Synthetic Hydrocarbon | VARIOUS | 80-100 |
| Petroleum Distillates, Solvent-dewaxed Heavy Paraffinic | 64742-65-0 | <2 |

All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

4. FIRST AID MEASURES

First aid measures

General advice In case of accident or if you feel unwell, seek medical advice immediately (show directions

for use or safety data sheet if possible).

Inhalation Remove to fresh air and keep at rest in a position comfortable for breathing. If symptoms

occur get medical attention.

Skin contact Wash skin with plenty of soap and water. If irritation or other symptoms occur get medical

attention. Any injection injury from high pressure equipment should be evaluated immediately by a physician as potentially serious (See NOTES TO PHYSICIAN).

Eye contact Immediately flush eyes with plenty of water. Eyelids should be held away from the eyeball to

ensure thorough rinsing. Gently remove contacts while flushing. If irritation or other

symptoms occur get medical attention.

Ingestion Rinse mouth out with water. Do not induce vomiting unless directed by a physician. If

spontaneous vomiting occurs, keep head below hips, or if patient is lying down, turn body and head to side to prevent aspiration and monitor for breathing difficulty. If symptoms

develop, seek medical attention.

Most important signs and symptoms, both short-term and delayed with overexposure

Adverse effects Prolonged or repeated inhalation of oil mist at high concentrations may cause respiratory

irritation and/or other pulmonary effects. Prolonged and repeated skin contact may cause

defatting and drying of the skin and may lead to irritation and/or dermatitis.

Indication of any immediate medical attention and special treatment needed

Notes to physician SKIN: Leaks or accidents involving high-pressure equipment may inject a stream of material

through the skin and initially produce an injury that may not appear serious. Only a small puncture wound may appear on the skin surface but, without proper treatment and depending on the nature, original pressure, volume, and location of the injected material, can compromise blood supply to an affected body part. Prompt surgical debridement of the wound may be necessary to prevent irreversible loss of function and/or the affected body part. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing mediaFor small fires, Class B fire extinguishing media such as CO2, dry chemical, foam or water spray can be used. For large fires, water spray, fog or foam can be used. Firefighting should

SDS ID NO.: 0644MAR019 Product name Marathon Pro EP Gear Oil Full Syn Page 2 of 8

be attempted only by those who are adequately trained and equipped with proper protective

Revision date 07/18/2025

equipment.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the

chemical

The product is not combustible per the OSHA Hazard Communication Standard, but will

ignite and burn at temperatures exceeding the flash point.

Hazardous combustion products Smoke, carbon monoxide, and other products of incomplete combustion.

Explosion data

Sensitivity to mechanical impact:No. Sensitivity to static discharge:

Special protective equipment and precautions for firefighters

Avoid using straight water streams. Water spray and foam must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Use water spray to cool exposed surfaces from as far a distance as possible. Keep run-off

water out of sewers and water sources.

Additional firefighting tactics Not applicable

NFPA Health 1 Instability 0 Special Hazard -Flammability 1

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Keep people away from and upwind of spill/leak. Contaminated surfaces may be slippery.

Use personal protection measures as recommended in Section 8. **Protective equipment**

Emergency procedures Advise authorities and National Response Center (800-424-8802) if the product has entered

a water course or sewer. Notify local health and pollution control agencies, if appropriate.

Environmental precautions Avoid release to the environment. Avoid subsoil penetration.

Methods and materials for

containment

Stop leak if you can do it without risk. Prevent spilled material from entering storm drains, sewers, and open waterways. Move containers from spill area. Contain liquid with sand or

soil.

Methods and materials for cleaning Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids. Recover and return free product to proper containers. Dispose of in accordance with local/regional/national regulations.

7. HANDLING AND STORAGE

Safe handling precautions

Avoid contact with skin, eyes and clothing. Do not swallow. Avoid breathing vapors or mists. Use good personal hygiene practices. Wash thoroughly after handling. Use personal protection measures as recommended in Section 8. Do not cut, drill, grind, puncture, weld or incinerate container. Empty container may contain hazardous residue. Refer to applicable EPA, OSHA, NFPA and consistent state and local requirements.

High-pressure injection of any material through the skin is a serious medical emergency even though the small entrance wound at the injection site may not initially appear serious. These injection injuries can occur from high-pressure equipment such as paint spray or grease or guns, fuel injectors, or pinhole leaks in hoses or hydraulic lines and should all be considered serious. High pressure injection injuries may be SERIOUS SURGICAL

EMERGENCIES (See First Aid Section 4).

Store in properly closed containers that are appropriately labeled and in a cool, Storage conditions

well-ventilated area. Containers that have been opened must be carefully resealed and kept

upright to prevent leakage. Store away from incompatible materials.

SDS ID NO.: 0644MAR019 Product name Marathon Pro EP Gear Oil Full Syn Page 3 of 8

Incompatible materials. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

| Chemical Name | ACGIH TLV | OSHA PELS | NIOSH IDLH |
|--|-------------|--------------------------|------------------------------|
| Synthetic Hydrocarbon | 5 mg/m³ TWA | TWA: 5 mg/m ³ | IDLH: 2500 mg/m ³ |
| VARIOUS | (oil mist) | (oil mist) | (oil mist) |
| Petroleum Distillates, Solvent-dewaxed | | TWA: 5 mg/m ³ | IDLH: 2500 mg/m ³ |
| Heavy Paraffinic | (oil mist) | (oil mist) | (oil mist) |
| 64742-65-0 | | | |

Notes: No further information available.

Engineering measuresLocal or general exhaust required when using at elevated temperatures that generate

vapors or mists. Local or general exhaust required to maintain vapors below established

Revision date 07/18/2025

limits.

Personal protective equipment

Eye protection Use goggles or face-shield if the potential for splashing exists.

Skin and body protection Wear neoprene, nitrile or PVA gloves to prevent skin contact. Glove suitability is based on

workplace conditions and usage. Contact the glove manufacturer for specific advice on

glove selection and breakthrough times. Wear appropriate protective clothing.

Respiratory protectionUse a NIOSH approved organic vapor chemical cartridge or supplied air respirators when

there is the potential for airborne exposures to exceed permissible exposure limits or if excessive vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 29 CFR 1910.134. Self-contained breathing apparatus should

be used for fire fighting.

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes and clothing. Wash hands before breaks and immediately after handling the

product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Amber Liquid
Physical State Liquid
Color Amber
Odor Petroleum
Odor Threshold No data available.

Property
pH
No available data.

Melting Point / Freezing Point
Initial Boiling Point / Boiling Range
Flash Point
Evaporation Rate
Flammability (solid, gas)

Values (method)
No available data.
No data available.
Vo data available.
No data available.
Not applicable.

Flammability Limit in Air (%):

Upper Flammability Limit:
Lower Flammability Limit:
No data available.
No data available.
No data available.
Vapor Pressure

No mata available.
Vapor Pressure

No mata available.

Vapor Density >1 Specific Gravity / Relative Density 0.85

SDS ID NO.: 0644MAR019 Product name Marathon Pro EP Gear Oil Full Syn Page 4 of 8

0644MAR019 Marathon Pro EP Gear Oil Full Syn

Revision date 07/18/2025

Water Solubility
Partition Coefficient
Autoignition Temperature
Decomposition Temperature
Kinematic Viscosity

Insoluble in water
No data available.
No data available.
No data available.
220-460 cSt @ 40°C

VOC Content (%)

Particle characteristics

Kst

No data available.

No data available.

10. STABILITY AND REACTIVITY

Reactivity The product is non-reactive under normal conditions.

Chemical stability Stable under recommended storage conditions.

Possibility of hazardous reactions
None under normal processing.

Hazardous polymerization Will not occur.

Conditions to avoid Sources of heat or ignition.

Incompatible materials. Strong oxidizing agents.

Hazardous decomposition products None known under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Potential short-term adverse effects from overexposures

Inhalation Inhalation of high vapor concentrations may cause irritation of the respiratory system.

Eye contact Exposure to vapor or contact with liquid may cause mild eye irritation, including tearing,

stinging, and redness.

Skin contact Prolonged or repeated exposure may cause dermatitis, folliculitis or oil acne.

Ingestion May cause irritation of the mouth, throat and gastrointestinal tract.

Acute toxicological data

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|----------------------------------|---------------------|-----------------------|------------------------|
| Petroleum Distillates, | > 15000 mg/kg (Rat) | > 5000 mg/kg (Rabbit) | > 2400 mg/m³ (Rat) 4 h |
| Solvent-dewaxed Heavy Paraffinic | > 24 g/kg (Rat) | | 2062 ppm (Rat) 4 h |
| 64742-65-0 | | | |

Immediate and delayed effects as well as chronic effects from short and long-term exposure

This product is considered to have a low order of acute and chronic toxicity under normal use and storage conditions

Adverse effects related to the physical, chemical and toxicological characteristics

Signs and symptoms Prolonged or repeated inhalation of oil mist at high concentrations may cause respiratory

irritation and/or other pulmonary effects. Prolonged and repeated skin contact may cause

defatting and drying of the skin and may lead to irritation and/or dermatitis.

Acute toxicity None known.

Skin corrosion/irritation None known.

Serious eye damage/eye irritation None known.

SDS ID NO.: 0644MAR019 Product name Marathon Pro EP Gear Oil Full Syn Page 5 of 8

Revision date 07/18/2025

Sensitization None known.

Mutagenic effects None known.

Prolonged or repeated contact with used lube oils may cause skin cancer. Carcinogenicity

Reproductive toxicity None known.

Specific Target Organ Toxicity

(STOT) - single exposure

None known.

Specific Target Organ Toxicity

(STOT) - repeated exposure

None known.

Aspiration hazard None known.

12. ECOLOGICAL INFORMATION

Used motor and/or lube oils may be toxic to birds and fish. **Ecotoxicity**

| Chemical Name | Fish | Crustacea | Algae/aquatic plants |
|---|------------------------|------------------------|----------------------|
| Petroleum Distillates, | 96-hr LC50 = 5000 mg/l | 48-hr EC50 = 1000 mg/l | - |
| Solvent-dewaxed Heavy Paraffinic 64742-65-0 | Rainbow Trout | Daphnia magna | |

Persistence and degradability Not expected to be readily biodegradable.

No information available. **Bioaccumulation**

Mobility in soil No information available.

No information available. Other adverse effects

13. DISPOSAL CONSIDERATIONS

Description of waste residues No information available.

Handle in accordance with applicable local, state, and federal regulations. Use personal Safe handling of wastes

protection measures as required.

Disposal of wastes / methods of

disposal

The user is responsible for determining if any discarded material is a hazardous waste (40

CFR 262.11). Dispose of in accordance with federal, state and local regulations.

Empty containers should be completely drained and then discarded or recycled, if possible. Contaminated packaging disposal

Do not cut, drill, grind or weld on empty containers since explosive residues may be present.

Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT

UN/Identification No: Not applicable **UN Proper Shipping Name:** Not applicable. Not applicable Transport Hazard Class(es): Not applicable **Packing Group:**

IATA

UN/Identification No: Not applicable **UN Proper Shipping Name:** Not Regulated

SDS ID NO.: 0644MAR019 Product name Marathon Pro EP Gear Oil Full Syn Page 6 of 8

0644MAR019 Marathon Pro EP Gear Oil Full Syn

Transport Hazard Class(es):

Packing Group:

Not applicable
Not applicable

IMDG

UN/Identification No:
UN Proper Shipping Name:
Transport Hazard Class(es):
Packing Group:

Not applicable
Not applicable
Not applicable

15. REGULATORY INFORMATION

Regulatory Information

US TSCA Chemical Inventory

This product and/or its components are listed on the TSCA Chemical Inventory or are

exempt.

Canada DSL/NDSL Inventory

This product and/or its components are listed either on the Domestic Substances List (DSL)

or are exempt.

EPA Superfund Amendment & Reauthorization Act (SARA)

SARA Section 302 This product is not known to contain any component(s) included on EPA's Extremely

Hazardous Substance (EHS) List above the de minimis threshold.

SARA Section 304 This product does not contain any component(s) identified as an EHS or a CERCLA

Hazardous substance above the de minimis threshold.

SARA Section 311/312 Not applicable.

SARA Section 313 This product is not known to contain components, which if in exceedance of the de minimus

threshold, may be subject to the reporting requirements of SARA Title III Section 313 Toxic

Revision date 07/18/2025

Release Reporting (Form R).

U.S. State Regulations

California Proposition 65 This product is not known to contain chemicals known to the State of California to cause

cancer, birth defects or other reproductive harm.

For more information, go to www.P65Warnings.ca.gov.

State Right-To-Know Regulations This material is not known to be identified on any State Right-To-Know regulation list.

| Chemical Name | New Jersey Right-To-Know | Pennsylvania Right-To-Know | Massachusetts Right-To Know |
|------------------------|--------------------------|----------------------------|-----------------------------|
| Petroleum Distillates, | Listed | Listed | Listed |
| Solvent-dewaxed Heavy | | | |
| Paraffinic | | | |
| 64742-65-0 | | | |

16. OTHER INFORMATION

<u>Prepared by</u> Toxicology & Product Safety

NFPA

SDS ID NO.: 0644MAR019 Product name Marathon Pro EP Gear Oil Full Syn Page 7 of 8

Revision date 07/18/2025



Revision Notes

Revision date 07/18/2025

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SDS ID NO.: 0644MAR019 Product name Marathon Pro EP Gear Oil Full Syn Page 8 of 8