



SDS ID NO.: 0326MAR019 **Revision date** 04/26/2023

1. IDENTIFICATION

Product Name Marathon Multipower-3 Full Synthetic CK-4 (5W-40)

Synonym Multipower-3 Full Synthetic 5W-40 (CK-4); Heavy duty motor oil

Product code 0326MAR019 Chemical family Motor/Lube Oil

Recommended use Engine Oil.
Restrictions on use Engine Oil.

Manufacturer, Importer, or Responsible Party Name and

Address

MARATHON PETROLEUM COMPANY LP

539 South Main Street Findlay, OH 45840

SDS information 1-419-421-3070 (M-F; 8-5 EST)

24 Hour Emergency Telephone CHEMTREC: 1-800-424-9300 (CCN# 13740)

2. HAZARD IDENTIFICATION

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Classification

Serious eye damage/eye irritation	Category 2A
Reproductive toxicity	Category 1

Hazards Not Otherwise Classified (HNOC)

Not applicable

2.2. Label Elements

Warning

Causes serious eye irritation
May damage fertility



Appearance Brown Liquid Physical State Liquid Odor Petroleum

Precautionary Statements - Prevention

SDS ID NO.: 0326MAR019

Product name Marathon Multipower-3 Full Synthetic CK-4 (5W-40)

Page 1 of 9

Revision date 04/26/2023

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear eve/face protection

Wash hands and any possibly exposed skin thoroughly after handling

Precautionary Statements - Response

IF exposed or concerned: Get medical attention

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container at an approved waste disposal plant

Additional Information

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition Information

Chemical Name	CAS Number	% Concentration
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	30-60
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	68037-01-4	7-13
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	3-7
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	1-5
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	113706-15-3	0.5-1.5
Phenol, (tetrapropenyl) derivitives	74499-35-7	0.1-1

Motor oil is a complex mixture of highly refined lubricating oil base stocks and additives. All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

4. FIRST AID MEASURES

First aid measures

General advice In case of accident or if you feel unwell, seek medical advice immediately (show directions

for use or safety data sheet if possible).

Inhalation Remove to fresh air and keep at rest in a position comfortable for breathing. If symptoms

occur get medical attention.

Skin contact Wash skin with plenty of soap and water. If irritation or other symptoms occur get medical

attention. Wash contaminated clothing and clean shoes before reuse. Any injection injury from high pressure equipment should be evaluated immediately by a physician as

potentially serious (See NOTES TO PHYSICIAN).

Flush immediately with large amounts of water for at least 15 minutes. Gently remove Eve contact

contacts while flushing. Eyelids should be held away from the eyeball to ensure thorough

rinsing. Get medical attention.

Rinse mouth out with water. Do not induce vomiting unless directed by a physician. If Ingestion

spontaneous vomiting occurs, keep head below hips, or if patient is lying down, turn body and head to side to prevent aspiration and monitor for breathing difficulty. If symptoms

develop, seek medical attention.

Most important signs and symptoms, both short-term and delayed with overexposure

Adverse effects Causes eye irritation. Symptoms may include redness, itching, and inflammation. Prolonged

or repeated inhalation of oil mist at high concentrations may cause respiratory irritation and/or other pulmonary effects. Prolonged and repeated skin contact may cause defatting

and drying of the skin and may lead to irritation and/or dermatitis.

Indication of any immediate medical attention and special treatment needed

No.

SKIN: Leaks or accidents involving high-pressure equipment may inject a stream of material Notes to physician

> through the skin and initially produce an injury that may not appear serious. Only a small puncture wound may appear on the skin surface but, without proper treatment and depending on the nature, original pressure, volume, and location of the injected material, can compromise blood supply to an affected body part. Prompt surgical debridement of the wound may be necessary to prevent irreversible loss of function and/or the affected body part. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES.

5. FIRE-FIGHTING MEASURES

For small fires, Class B fire extinguishing media such as CO2, dry chemical, foam or water Suitable extinguishing media

> spray can be used. For large fires, water spray, fog or foam can be used. Firefighting should be attempted only by those who are adequately trained and equipped with proper

protective equipment.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the

chemical

The product is not combustible per the OSHA Hazard Communication Standard, but will

ignite and burn at temperatures exceeding the flash point.

Hazardous combustion products Smoke, carbon monoxide, and other products of incomplete combustion.

Explosion data

Sensitivity to mechanical

impact:

Sensitivity to static discharge: No.

Special protective equipment and

precautions for firefighters

SDS ID NO.: 0326MAR019

Avoid using straight water streams. Water spray and foam must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Use water spray to cool exposed surfaces from as far a distance as possible.

Keep run-off water out of sewers and water sources.

Additional firefighting tactics Not applicable

Instability 0 **NFPA** Health 1 Flammability 1 Special Hazard -

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Keep public away. Isolate and evacuate area. Shut off source if safe to do so. All

contaminated surfaces will be slippery.

Use personal protection measures as recommended in Section 8. **Protective equipment**

Emergency procedures Advise authorities and National Response Center (800-424-8802) if the product has

entered a water course or sewer. Notify local health and pollution control agencies, if

appropriate.

Avoid release to the environment. Avoid subsoil penetration. **Environmental precautions**

Methods and materials for containment

Stop leak if you can do it without risk. Prevent spilled material from entering storm drains, sewers, and open waterways. Move containers from spill area. Contain liquid with sand or soil.

Methods and materials for cleaning

Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids. Recover and return free product to proper containers. Dispose of in accordance with local/regional/national regulations.

7. HANDLING AND STORAGE

Safe handling precautions

Avoid contact with skin, eyes and clothing. Do not swallow. Avoid breathing vapors or mists. Use good personal hygiene practices. Wash thoroughly after handling. Use personal protection measures as recommended in Section 8. Do not cut, drill, grind, puncture, weld or incinerate container. Empty container may contain hazardous residue. Refer to applicable EPA, OSHA, NFPA and consistent state and local requirements.

High-pressure injection of any material through the skin is a serious medical emergency even though the small entrance wound at the injection site may not initially appear serious. These injection injuries can occur from high-pressure equipment such as paint spray or grease or guns, fuel injectors, or pinhole leaks in hoses or hydraulic lines and should all be considered serious. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES (See First Aid Section 4).

Storage conditions

Store in properly closed containers that are appropriately labeled and in a cool, well-ventilated area. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from incompatible materials.

Incompatible materials

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical Name	ACGIH TLV	OSHA PELS	NIOSH IDLH
Petroleum Base Oils MIXTURE	Highly and severely refined, inhalable fraction 5 mg/m³ TWA	TWA: 5 mg/m³	2500 mg/m³

Notes:

No further information available.

Engineering measures

Local or general exhaust required when using at elevated temperatures that generate vapors or mists.

Personal protective equipment

Eye protection

Use goggles or face-shield if the potential for splashing exists.

Skin and body protection

Wear neoprene, nitrile or PVA gloves to prevent skin contact. Glove suitability is based on workplace conditions and usage. Contact the glove manufacturer for specific advice on glove selection and breakthrough times. Wear appropriate protective clothing.

Respiratory protection

Use a NIOSH approved organic vapor chemical cartridge or supplied air respirators when there is the potential for airborne exposures to exceed permissible exposure limits or if excessive vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 29 CFR 1910.134. Self-contained breathing apparatus should be used for fire fighting.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Brown Liquid
Physical State Liquid
Color Brown
Odor Petroleum
Odor Threshold No data available.

Property
pH
No available data.

Melting Point / Freezing Point
Initial Boiling Point / Boiling Range
No data available.

No data available.

Flash Point $> 200 \, ^{\circ}\text{C} \, / > 392 \, ^{\circ}\text{F} \, (ASTM \, D92)$

Evaporation Rate No data available. Flammability (solid, gas) Not applicable.

Flammability Limit in Air (%):

Upper Flammability Limit:
Lower Flammability Limit:
No data available.
No data available.
Vapor Pressure
Vapor Density
No data available.
No data available.
No data available.

Specific Gravity / Relative Density > 0.85

Water Solubility
Partition Coefficient
Autoignition Temperature
Decomposition Temperature
No data available.
No data available.
No data available.

Kinematic Viscosity > 80 cSt @ 40°C (ASTM D445)

VOC Content (%)

Bulk Density

No data available.

No data available.

10. STABILITY AND REACTIVITY

Reactivity The product is non-reactive under normal conditions.

Chemical stability Stable under recommended storage conditions.

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization Will not occur.

Conditions to avoid Sources of heat or ignition.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products None known under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Potential short-term adverse effects from overexposures

Inhalation Inhalation of high vapor concentrations may cause irritation of the respiratory system.

Eye contact Irritating to eyes. May cause reddening and tearing.

Skin contact Prolonged or repeated exposure may cause dermatitis, folliculitis or oil acne.

Ingestion May cause irritation of the mouth, throat and gastrointestinal tract.

Acute toxicological data

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum Base Oils	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5 mg/L (Rat) 4 h
MIXTURE			
Dec-1-ene, homopolymer,	-	-	> 5.2 mg/L (Rat) 4 h
hydrogenated Dec-1-ene,			
oligomers, hydrogenated			
68037-01-4			

Immediate and delayed effects as well as chronic effects from short and long-term exposure

BASE OILS: Mineral oil mists from highly refined or hydrotreated oils are generally of low acute and subchronic toxicity. Overexposure to mists may cause inflammation of the lungs and lipoid pneumonia.

USED MOTOR OIL: Lifetime, continuous skin contact with used motor oils has caused skin cancer in laboratory tests. The combustion process produces compounds (polycyclic aromatic hydrocarbons) in motor oils that increase with use and are responsible for the cancer induction. Thorough washing has been found to prevent the development of skin cancer on animals from used motor oil exposure.

ZDDP: Zinc dialkyldithiophosphate (ZDDP) additives are primarily eye and/or skin irritants or corrosives with low acute toxicity via oral, dermal, and inhalation routes of exposure and are not skin sensitizers. In laboratory repeat dose studies by the dermal and oral routes, ZDDPs cause effects only at high doses, primarily due to irritation, in a manner similar to other irritating materials. The weight-of- evidence of genotoxicity testing indicates that ZDDPs are not mutagenic and do not cause larger chromosomal effects.

Adverse effects related to the physical, chemical and toxicological characteristics

Signs and symptoms Causes eye irritation. Symptoms may include redness, itching, and inflammation. Prolonged

or repeated inhalation of oil mist at high concentrations may cause respiratory irritation and/or other pulmonary effects. Prolonged and repeated skin contact may cause defatting

and drying of the skin and may lead to irritation and/or dermatitis.

Acute toxicity None known.

Skin corrosion/irritation None known.

Serious eye damage/eye irritation Causes serious eye irritation.

Sensitization None known.

Mutagenic effects None known.

Carcinogenicity Prolonged or repeated contact with used engine oils may cause skin cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
	(Class)	(Class)		
Petroleum Base Oils	Mineral oil, highly/severely	Mineral oil, highly refined	Not Listed	Not Listed
MIXTURE	refined	Not Classifiable (3)		
	(inhalable fraction)	` ,		
	Not Classifiable (A4)			

Reproductive toxicity May damage fertility.

Specific Target Organ Toxicity (STOT) - single exposure

None known.

Specific Target Organ Toxicity (STOT) - repeated exposure

SDS ID NO.: 0326MAR019

None known.

Aspiration hazard None known.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Used motor and/or lube oils may be toxic to birds and fish.

Chemical Name	Fish	Crustacea	Algae/aquatic plants
Petroleum Base Oils	96-hr LC50 = 5000 mg/L	48-hr EC50 = 1000 mg/L	-
MIXTURE	Rainbow trout	Daphnia magna	

Persistence and degradability
Not expected to be readily biodegradable.

Bioaccumulation No information available.

Mobility in soil No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Description of waste residues No information available.

Safe handling of wastes Handle in accordance with applicable local, state, and federal regulations. Use personal

protection measures as required.

Disposal of wastes / methods of

disposal

The user is responsible for determining if any discarded material is a hazardous waste (40

CFR 262.11). Dispose of in accordance with federal, state and local regulations.

Contaminated packaging disposal Empty containers should be completely drained and then discarded or recycled, if possible.

Do not cut, drill, grind or weld on empty containers since explosive residues may be present. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

<u>DOT</u>

UN/Identification No:
UN Proper Shipping Name:
Not Regulated
Transport Hazard Class(es):
Not applicable
Packing Group:
Not applicable

<u>IATA</u>

UN/Identification No:Not applicableUN Proper Shipping Name:Not RegulatedTransport Hazard Class(es):Not applicablePacking Group:Not applicable

IMDG

UN/Identification No:
UN Proper Shipping Name:
Transport Hazard Class(es):
Packing Group:

Not applicable
Not applicable
Not applicable

15. REGULATORY INFORMATION

Regulatory Information

US TSCA Chemical Inventory

This product and/or its components are listed on the TSCA Chemical Inventory or are

exempt.

Canada DSL/NDSL Inventory This product and/or its components are listed either on the Domestic Substances List (DSL)

or are exempt.

EPA Superfund Amendment & Reauthorization Act (SARA)

SARA Section 302 This product does not contain any component(s) included on EPA's Extremely Hazardous

Substance (EHS) List above the de minimis threshold.

SARA Section 304 This product does not contain any component(s) identified as an EHS or a CERCLA

Hazardous substance above the de minimis threshold.

SARA Section 311/312 The following EPA hazard categories apply to this product:

Serious eye damage or eye irritation

Reproductive toxicity

SARA Section 313 This product may contain component(s), which if in exceedance of the de minimus

threshold, may be subject to the reporting requirements of SARA Title III Section 313 Toxic

Release Reporting (Form R).

Chemical Name	CERCLA/SARA 313 Emission reporting
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl)	1.0 % de minimis concentration
esters, zinc salts	
113706-15-3	

U.S. State Regulations

SDS ID NO.: 0326MAR019

California Proposition 65 This product can expose you to chemicals which are known to the State of California to

cause cancer, birth defects or other reproductive harm.

Chemical Name	California Proposition 65	
Benzene	Carcinogen, initial date 02/27/1987	
71-43-2	Male developmental toxicity, initial date 12/26/1997	
Lead and Lead Compounds, inorganic	Carcinogen, initial date 10/1/92	
7439-92-1	Developmental toxicity, initial date 2/27/87	
	Reproductive toxicity, initial date 2/27/87	
Nickel and compounds	Carcinogen, initial date 10/1/1989 (metallic)	
7440-02-0		
Toluene	Developmental toxicity, initial date 01/01/1991	
108-88-3		
Ethanediol	Developmental toxicity (ingested), initial date 06/19/2015	
107-21-1		

For more information, go to www.P65Warnings.ca.gov.

State Right-To-Know Regulations The following component(s) of this material are identified on the regulatory lists below:

Chemical Name	New Jersey Right-To-Know	Pennsylvania Right-To-Know	Massachusetts Right-To Know
Petroleum Base Oils MIXTURE	Listed	Listed	Listed
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts 113706-15-3	Listed	Listed	Not Listed

16. OTHER INFORMATION

Prepared by Toxicology & Product Safety

NFPA



Revision Notes

Revision date Previous publish date Revised sections 04/26/2023

11/06/2017

1. IDENTIFICATION

2. HAZARD IDENTIFICATION

3. COMPOSITION/INFORMATION ON INGREDIENTS

7. HANDLING AND STORAGE

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

9. PHYSICAL AND CHEMICAL PROPERTIES

11. TOXICOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

15. REGULATORY INFORMATION

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.